

Details:

- LinearLight 2W-TW5.9 is a small profile, IP68 wet listed tunable white LED strip with best-in-class CRI available for a variety of applications. LinearLight 2W-TW5.9 is provided in an output of 360lm/ft.
- Stocked in 192" lengths but can be factory cut and delivered to project site based on site specific measurements by the Convey Team.

Physical Features:

- Factory cut lengths to 1.64" Increments.
- Complete factory assembly with any Series BE2 Profiles.
- 96" Power Leads

Lighting Features:


- 120° beam spread
- 50,000hr. Life (L70)
- 5 year warranty
- TM-30 data available at www.conveylighting.com



Profile:



*Image of LightLine2 prior to silicone injection process for IP68 rating



Specifications:

Average Power Consumption	5.9W/ft.
Voltage	24V/dc
Binning	3 step
Cut Increment	1.64"
Diodes per foot	87
Max. Run	16ft.
IP Rating	IP68 (Class II wet location)
Dimensions	0.47"W x 0.16"H

CCT	Lumen Output (lm/ft.)	Efficacy (lm/W)
2700K, 6500K @98CRI	360	62
2200K@90CRI, 4000K @98CRI	360	62
2200K@90CRI, 3000K @98CRI	360	62

Ordering Information:

Example:
L2W-TW5.9-27/65-30'

Model: - CCT: - Length: - Transformer/PSU:

L2W-TW5.9 5.9W/ft. **27/65** 2700K/6500K **1'-16'** SPECIFY CUSTOM **TXXX** SPECIFIED SEPARATELY
22/40 2200K/4000K **C**
22/30 2200K/3000K