

LinearLight 2-SW6.1HE (High Efficacy)

CONVEY

Details:

- LinearLight 2-SW6.1HE is a small profile, versatile LED strip with best-in-class CRI available for a variety of applications. LinearLight 2-SW6.1HE is provided in outputs up to 1036m/ft.
- Stocked in 22.9' lengths but can be factory cut and delivered to project site based on site specific measurements by the Convey Team.

Physical Features:


- Factory cut lengths to 1.31" Increments with run length up to 22.9'.
- 3M (300LSE) yellow adhesive tape attached on backside, standard
- Complete factory assembly with any Series BE2 Profiles.
- 96" Power Leads

Lighting Features:

- 120° beam spread
- 50,000hr. Life (L70)
- 5 year warranty
- TM-30 data available at www.conveylighting.com



Profile:



Specifications:

Average Power Consumption	6.1W/ft.
Voltage	24V/dc
Binning	3 step
Cut Increment	1.31"
Diodes per foot	73
Max. Run	22.9ft.
IP Rating	IP20 (Class II dry location)
Dimensions	0.39"W x 0.07"H

CCT	Lumen Output (lm/ft.)	Efficacy (lm/W)
1800K @90CRI	760	125
2200K @90CRI	792	130
2400K @95CRI	824	135
2700K @98CRI	860	141
3000K @98CRI	895	146
3500K @98CRI	932	153
4000K @98CRI	1036	170

Ordering Information:

Example:
L2-SW6.1HE-30-32'

Model:

CCT:

Length:

Transformer/PSU

L2-SW6.1HE 6.1W/ft.

18 1800K, 90CRI
22 2200K, 90CRI
24 2400K, 95CRI
27 2700K, 98CRI
30 3000K, 98CRI
35 3500K, 98CRI
40 4000K, 98CRI

1'-16' SPECIFY
C CUSTOM

TXXX SPECIFIED
SEPARATELY



LM-80

