

CONVEY

- LinearLight 2-COB is a small profile, versatile LED strip with best-in-class CRI available for a variety of applications. LinearLight 2-COB is provided an average output of 302lm/ft
- Stocked in 192" lengths but can be factory cut and delivered to project site based on site specific measurements by the Convey Team.

- Factory cut lengths to 1.64" Increments with diode free illumination.
- 3M (300LSE) yellow adhesive tape attached on backside, standard.
- Suitable for all BE2 Profiles.
- 96" Power Leads standard.

- 150° beam spread
- 50,000hr. Life (L70)
- 5 year warranty
- TM-30 data available at www.conveylighting.com



Technical drawing of a cable assembly. The drawing shows a cable with a braid and a shield, and a cable with a shield and a shield. The dimensions are given in inches [mm].

Dimensions:

- Overall length: 5000 [196.85]
- Section 1 length: 41.67 [1.64]
- Section 2 length: 18.18 [0.72]
- Section 3 length: 18.18 [0.72]
- Section 4 length: 18.18 [0.72]
- Section 5 length: 18.18 [0.72]
- Section 6 length: 18.18 [0.72]
- Section 7 length: 18.18 [0.72]
- Section 8 length: 18.18 [0.72]
- Section 9 length: 18.18 [0.72]
- Section 10 length: 18.18 [0.72]
- Section 11 length: 18.18 [0.72]
- Section 12 length: 18.18 [0.72]
- Section 13 length: 18.18 [0.72]
- Section 14 length: 18.18 [0.72]
- Section 15 length: 18.18 [0.72]
- Section 16 length: 18.18 [0.72]
- Section 17 length: 18.18 [0.72]
- Section 18 length: 18.18 [0.72]
- Section 19 length: 18.18 [0.72]
- Section 20 length: 18.18 [0.72]
- Section 21 length: 18.18 [0.72]
- Section 22 length: 18.18 [0.72]
- Section 23 length: 18.18 [0.72]
- Section 24 length: 18.18 [0.72]
- Section 25 length: 18.18 [0.72]
- Section 26 length: 18.18 [0.72]
- Section 27 length: 18.18 [0.72]
- Section 28 length: 18.18 [0.72]
- Section 29 length: 18.18 [0.72]
- Section 30 length: 18.18 [0.72]
- Section 31 length: 18.18 [0.72]
- Section 32 length: 18.18 [0.72]
- Section 33 length: 18.18 [0.72]
- Section 34 length: 18.18 [0.72]
- Section 35 length: 18.18 [0.72]
- Section 36 length: 18.18 [0.72]
- Section 37 length: 18.18 [0.72]
- Section 38 length: 18.18 [0.72]
- Section 39 length: 18.18 [0.72]
- Section 40 length: 18.18 [0.72]
- Section 41 length: 18.18 [0.72]
- Section 42 length: 18.18 [0.72]
- Section 43 length: 18.18 [0.72]
- Section 44 length: 18.18 [0.72]
- Section 45 length: 18.18 [0.72]
- Section 46 length: 18.18 [0.72]
- Section 47 length: 18.18 [0.72]
- Section 48 length: 18.18 [0.72]
- Section 49 length: 18.18 [0.72]
- Section 50 length: 18.18 [0.72]
- Section 51 length: 18.18 [0.72]
- Section 52 length: 18.18 [0.72]
- Section 53 length: 18.18 [0.72]
- Section 54 length: 18.18 [0.72]
- Section 55 length: 18.18 [0.72]
- Section 56 length: 18.18 [0.72]
- Section 57 length: 18.18 [0.72]
- Section 58 length: 18.18 [0.72]
- Section 59 length: 18.18 [0.72]
- Section 60 length: 18.18 [0.72]
- Section 61 length: 18.18 [0.72]
- Section 62 length: 18.18 [0.72]
- Section 63 length: 18.18 [0.72]
- Section 64 length: 18.18 [0.72]
- Section 65 length: 18.18 [0.72]
- Section 66 length: 18.18 [0.72]
- Section 67 length: 18.18 [0.72]
- Section 68 length: 18.18 [0.72]
- Section 69 length: 18.18 [0.72]
- Section 70 length: 18.18 [0.72]
- Section 71 length: 18.18 [0.72]
- Section 72 length: 18.18 [0.72]
- Section 73 length: 18.18 [0.72]
- Section 74 length: 18.18 [0.72]
- Section 75 length: 18.18 [0.72]
- Section 76 length: 18.18 [0.72]
- Section 77 length: 18.18 [0.72]
- Section 78 length: 18.18 [0.72]
- Section 79 length: 18.18 [0.72]
- Section 80 length: 18.18 [0.72]
- Section 81 length: 18.18 [0.72]
- Section 82 length: 18.18 [0.72]
- Section 83 length: 18.18 [0.72]
- Section 84 length: 18.18 [0.72]
- Section 85 length: 18.18 [0.72]
- Section 86 length: 18.18 [0.72]
- Section 87 length: 18.18 [0.72]
- Section 88 length: 18.18 [0.72]
- Section 89 length: 18.18 [0.72]
- Section 90 length: 18.18 [0.72]
- Section 91 length: 18.18 [0.72]
- Section 92 length: 18.18 [0.72]
- Section 93 length: 18.18 [0.72]
- Section 94 length: 18.18 [0.72]
- Section 95 length: 18.18 [0.72]
- Section 96 length: 18.18 [0.72]
- Section 97 length: 18.18 [0.72]
- Section 98 length: 18.18 [0.72]
- Section 99 length: 18.18 [0.72]
- Section 100 length: 18.18 [0.72]

Average Power Consumption	5.5W/ft.
Voltage	24V/dc
Binning	3 step
Cut Increment	1.64"
Diodes per foot	256
Max. Run	16ft.
IP Rating	IP20 (Dry location) or IP67 (Wet)
Dimensions	0.47"W x 0.06"H (* See IP67 Note)

CCT	Lumen Output (lm/ft.)	Efficacy (lm/W)
ALL ON @90CRI	302	55
RED Only	30	18
GREEN Only	78	47
BLUE Only	85	51
2700K Only	85	51

Model: CCT: Length: Transformer/PSU:

L2COB-RGBTW5.5 5.5W/ft. **27/65** 2700K-6500K **1'-16'** SPECIFY CUSTOM **TXXX** SPECIFIED SEPARATELY

(*) L2COBW IP67 Version dimensions increase to 0.55"W x 0.16"H



1 BIN/3-STEP