

Details:

- Flexible and Dual Axis Bendable LED profile.
- Standard product is IP67 Rated for indoor and outdoor use.
- "Dot" Free



Features:

- Cut Segments in any length up to 16.4'
- Mounting via brackets, clips, straight or curved channel.
- Factory Cutting and Kiting Suggested.
- Power Leads and Connectors included at no charge.


Lighting Features:

- 120° beam spread
- 50,000hr. Life (L70) Indoors and 36,000hr Outdoors
- 90CRI Standard
- TM-30 data available at www.conveylighting.com

Also available in Static White, Tunable White and RGBW Options

**Feed Options:****Specifications:**


Average Power Consumption	4.27w per Foot
Voltage	24v DC
Binning	3 step
Cut Increment	Any Length cutting up to 16.4'
Lumens @ 3000k / 90CRI	235lm/ft
Max. Connection	16.4'
IP Rating	IP67 Standard
Beam Angle	120 Degrees

Sectional**Ordering Information:**

Example:
FLEX3-5W-WD-18/30-24-E-MC

Model:	CCT(White):	Voltage:	Feed Type:	Mounting:
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
FLEX3-5W-WD	18/30 1800/3000k 22/30 2200/3000k	24 24v DC	E End Feed S Side Feed B Back Feed	MC Clip MB Bracket MPS Profile Straight MPF Profile Flexible

Mounting:



LM-80

