Details:

- Flexible Top Bendable LED profile.
- Standard product is IP68 Rated for indoor and outdoor use in Pools with UL676 certification.
- "Dot" Free illumination.

Features:


- Cut Segments in any length up to 16.4'
- · Mounting via brackets, clips, and straight channel.
- · Factory Cutting only. This product cannot be field cut or modified.
- Standard with 157" Factory applied power feed.
- · Available in White Finish.

Lighting Features:

- 120° beam spread
- · 3 Year Warranty (*)
- 90CRI Standard
- TM-30 data available at www.conveylighting.com




Feed Options:



Specifications:

Average Power Consumption	4.3W per Foot
Voltage	24V
Binning	3 step
Cut Increment	Any Length cutting up to 16.4'
Lumens @ 4000k / 90CRI	213lm/ft
Max. Connection	16.4'
IP Rating	IP68 Standard / UL676 Pools
Beam Angle	120 Degrees

Sectional View







Refer to Side Bend (SB) Spec Sheet

Mounting:

'MC" Clip

"MB" Bracket

MPS" Profile

Ordering Information:

Example:

FLEX2-AQUA-TB-SW4.3-27-24-E-MB

35

3500K, 90CRI 40 4000K, 90CRI

Voltage: Feed Type: Mounting: CCT(White): Model: E 18 1800K 90CRI 24 24V DC End Feed MC FLEX2-AQUA-TB-SW4.3 Clip 22 2200K, 90CRI S Side Feed MB Bracket 24 2400K, 90CRI В Back Feed MPS Profile Straight 27 2700K, 90CRI 30 3000K, 90CRI

Higher than 40k available as special order Minimum purchase may apply







