#### Details:

- · Flexible Side Bendable LED profile.
- · Standard product is IP68 Rated for indoor and outdoor use in Pools with UL676 certification.
- "Dot" Free illumination.

### Features:


- Cut Segments in any length up to 16.4'
- · Mounting via brackets, clips, and straight channel.
- · Factory Cutting only. This product cannot be field cut or modified.
- Standard with 157" Factory applied power feed.
- · Available in White Finish.

# **Lighting Features:**

- 120° beam spread
- · 3 Year Warranty (\*)
- 90CRI Standard
- TM-30 data available at www.conveylighting.com




# **Feed Options:**



## Specifications:

Average Power Consumption	4.3W per Foot
Voltage	24V
Binning	3 step
Cut Increment	Any Length cutting up to 16.4'
Lumens @ 4000k / 90CRI	142lm/ft
Max. Connection	16.4'
IP Rating	IP68 Standard / UL676 Pools
Beam Angle	120 Degrees

#### Sectional View







Refer to Top Bend (TB) Spec Sheet

Mounting:

'MC" Clip

"MB" Bracket

'MPS" Profile

# **Ordering Information:**

Example: FLEX2-AQUA-SB-TW4.3-27/65-24-E-MB

Voltage: Feed Type: Mounting: CCT(Warm/Cool): Model: 27/65 90CRI 24V DC E 24 End Feed MC FLEX2-AQUA-SB-TW4.3 Clip S Side Feed MB Bracket 2700-6500K В Back Feed MPS Profile Straight

Higher than 40k available as special order Minimum purchase may apply







