Details:

- LinearLight 2-COB is a small profile, versatile LED strip with best-in-class CRI available for a variety of applications. LinearLight 2-COB is provided an output of 320lm/ft @ 3000k
- · Stocked in 192" lengths but can be factory cut and delivered to project site based on site specific measurements by the Convey Team.

Physical Features:


- Factory cut lengths to 1.97" Increments with diode free illumination.
- 3M (300LSE) yellow adhesive tape attached on backside, standard.
- · Suitable for all BE2 Profiles.
- · 96" Power Leads standard.

Lighting Features:

- 150° beam spread
- 50,000hr. Life (L70)
- 5 year warranty
- TM-30 data available at www.conveylighting.com



Profile:



Specifications:

Average Power Consumption	4.3W/ft.	
Voltage	24V/dc	
Binning	3 step	
Cut Increment	1.97"	
Diodes per foot	172	
Max. Run	16ft.	
IP Rating	IP20 (Dry location) or IP67 (Wet)	
Dimensions	0.39"W x 0.09"H (* See IP67 Note)	

ССТ	Lumen Output (lm/ft.)	Dim Level
3000K @98CRI	320	100%
2900K @98CRI	160	50% Dim
2500K @98CRI	45	14% Dim
2000K @ 98CRI	20	6% Dim
1800K @ 98CRI	16	4% Dim

Ordering Information:

Example: L2COB-WD4.3-30-14'

Model:

4.3W/ft. **18/30** 1800K-3000k

Length: 1'-16' SPECIFY C **CUSTOM** Transformer/PSU

TXXX SPECIFIED **SEPARATELY**

L2COBW-WD4.3

L2COB-WD4.3

See Note on IP67

(*) L2COBW IP67 Version dimensions increase to 0.47"W x 0.16"H

CCT:







